



KEI has been at the forefront of India's wire and cable industry for the last 5 decades. We manufacture a range of specialized cables and are a crucial player in the domestic and retail segment. Since inception, we have firmly believed in the philosophy of constant growth and innovation. Customer satisfaction has always been our priority. A highly qualified, committed and experienced group of professionals strive to meet international standards and cater to the needs of a changing market. Our unblemished track record has earned us the patronage of leading industrial houses, project consultants and architects. In order to provide reliable and expedient services to our customers,

we have created manufacturing facilities at Silvassa, Chopanki, Bhiwadi and Pathredi. We employ state-of-the-art equipment and adhere to international safety and environmental norms. KEI was established in 1968 as a partnership company in the domestic wire segment. In the early seventies we started manufacturing switchboard cables and control, instrumentation and thermocouple extension cables including special application cables like fire retardant and low halogen cables. In 1993 we added power cables with PVC & XLPE insulation in our product line. Today KEI is a one-stop-shop when it comes to meeting cabling requirements for the domestic, power and industrial sectors.

KEI Industries Limited

REGISTERED AND CORPORATE OFFICE:

D-90, OKHLA INDUSTRIAL AREA PHASE-I, NEW DELHI-110020, TEL: +91-11-26818840/8642/0242 FAX: 26817225, 26811959

E-MAIL: info@kei-ind.com WEBSITE: www.kei-ind.com CIN NO: L74899DL1992PLC051527

Manufacturing Units

Bhiwadi KEI Industries Limited SP-919/20/922, Ricco Industrial Area, Phase-III, Bhiwadi, Dist. Alwar-301019 Rajasthan Tel: +91-1493-220106/221731 Fax: 221731 E-Mail: bhiwadi@kei-ind.com	Silvassa KEI Industries Limited 99/27, Madhuban Industrial Estate, Rakholi, Silvassa-396230 Dadra & Nagar Haveli Tel: +91-260-2644404/2630944 Fax: 2645896 E-Mail: silvassa@kei-ind.com	Chopanki KEI Industries Limited A-280/281/282/283/284, Ricco Industrial Area (Chopanki) Dist. Alwar-301019 Rajasthan Tel: +91-1493-260202/06 Fax: 260203 E-mail: chopanki@kei-ind.com
---	---	---

Pathredi
KEI Industries Limited
Plot No. SP2-874, Ind. Area Pathredi-301019
Bhiwadi (Alwar) Rajasthan (India)

Marketing Offices (India)

WEST

Marketing Office-Mumbai
KEI Industries Limited
Nirvan Corporate, 7th Floor, Opposite Aghadi Nagar,
Pump House, Rajmata Jibabi Road, Andheri (E),
Mumbai - 400093
Tel: +91-22-28239673, 28375642
Fax: +91-22-28258277 E-mail: mumbai@kei-ind.com

Ahmedabad
KEI Industries Limited
301, Sarthik Complex, Opp. ISCKON BRTS,
Satellite Road, Ahmedabad-380015, Mob: 9825795673
E-Mail: dharmin.maniar@kei-ind.com,
ahmedabad@kei-ind.com

Pune
KEI Industries Limited
Vasudha Equinox, Office No. 104, 4th Floor,
MoujeBopodi, Near Khadki Railway Station, Pune-411003
Tel: 020-65600891 / 65600892
Mob. +91-9850526730/9823295878/ 9922226699
E-Mail: pune@kei-ind.com

Nagpur
KEI Industries Limited
103, Misal Layout, Near Maharashtra School
Nagpur - 440014
Mr. Saranjeet S. Kohli, Mob: +91-9822473774
E-Mail: nagpur@kei-ind.com

Kolhapur
KEI Industries Limited
776/ 3/6 AmarnathHighs Building, Near AmarnathMandir
Ganesh Colony, Kalamba Road, Kolhapur - 416007
near d mart Sholapur
Tel: 9371104263 / 8291918940
E-Mail: kolhapur@kei-ind.com, rajaram.kamble@kei-ind.com

NORTH

Jaipur
KEI Industries Limited
Shivam Business Center, 405, 4th Floor,
Calgary Hospital Road, Pradhan Marg,
Malviya Nagar, Jaipur - 302017 (Rajasthan)
Phone No. + 91 141 5179279 Fax: +91 141 252 9404
Mobile: +91 99290 93711
E-Mail: jaipur@kei-ind.com

Noida
KEI Industries Limited
A-43 Ground Floor, Sector-64, Noida,
UP - 201301 • Ph.: 0120-4315467

SOUTH

Chennai
KEI Industries Limited
No.4, (Old No. 23) SIR, C P Ramasamy Road,
2ND Floor, Near Apollo Hospital
Alwarpet, Chennai-600018
Tel: +91-44-42009120
Fax: +91-44-42009130; 8939768405
E-Mail: victor@kei-ind.com, chennai@kei-ind.com

Kochi
KEI Industries Limited
Ground Floor, 71/957 Bava Memorial Building,
Thamkalkaerthi Nagar Road, Elamakkara,
PO Kochi (Kerala)-682026
Ph.: 99470 87535 E-Mail: cochin@kei-ind.com

EAST

Kolkata
KEI Industries Limited
Anhanth Benchmark, 4th Floor/113-F Matheshwartola
Road Ps:Tiljala, Kolkata: 700 046
Tel: 033 - 4062 0820/4062 0822 Fax: 033 - 40620821
E-Mail: kolkata@kei-ind.com

Ranchi
KEI Industries Limited
Golden Camp Warehouse, Old H B Road
Kokar, Ranchi - 834 001
Contact: 099340 11405 / 09810492658
E-Mail: jharkhand@kei-ind.com

Marketing Office (Overseas)

Dubai
KEI Industries Limited
Post Box No. 261739, Jebel Ali Free Zone, Dubai, U.A.E.
Tel: +971 4 881 2310, + 971 50 2112013
Fax: +971 4 881 2311 E-mail: keidubai@emirates.net.ae
/dubai@kei-ind.com Contact: Mr. Shri Tamhankar

Nigeria
(Marketing Representative)
E-mail: kunal.gupta@kei-ind.com
Contact: +234 809 9777786

Vapi/Silvassa/Daman
KEI Industries Limited
A1/302, Karmabhumi Residency,
Behind Golden Bakery, Nanakwada, Halar,
Valsad- 396001.
Mr. Harsh Desai, Mob: 9723455316
E-Mail: harsh.desai@kei-ind.com

Raipur
KEI Industries Limited
206, 2nd Floor, Harshit Corporate, Amanaka,
G.E. Road, Raipur, Chhattisgarh - 492001
Mr. Sumit Ganguly - 7581809898
Email: Chhatsgarh@kei-ind.com

Indore
KEI Industries Limited
NISB, 316, 317, 3rd Floor, New Siyaganj
Warehouse Road, Indore, - 452010 (MP)
Contact: 0731-4206080, 9826888885

Goa
KEI Industries Limited
House no.617, Housing Board Colony,
Camurimlkapusa Goa 403507.
Mr. Nilesh Parab
Ph.: 9890452484 E-Mail: goa@kei-ind.com

Solapur
KEI Industries Limited
37/10 phande app samratchowek
near d mart Sholapur
Mr. Shallesh Bajaj - Tel: +91-8291885625
E-Mail: shallesh.bajaj@kei-ind.com

Lucknow
KEI Industries Limited
102, 1st Floor, Saran Chamber-2, 5 Park Road,
Lucknow-226001 UP • Tel: 0522-4010752

Panipat
KEI Industries Limited
C/o Narinder Gupta Mob: +91-8950660777

Chandigarh
KEI Industries Limited
SCO 17, 1st Floor, SwastikVihar, Mdc, Sector-5,
Panchkula-134109 Tel: +91-172-4416301
Fax: 4416300 E-Mail: chandigarh@kei-ind.com

Bangalore
KEI Industries Limited
No 15, Sirur Park Road, Sheshadripuram,
Bangalore-560029
Tel: +91-80-23466254, +91-80-23466260/55
E-Mail: bangalore@kei-ind.com

Hyderabad
KEI Industries Limited
Plot No. 76, H.No. 3-14-52/1, Shubodaya Colony,
Near Little Chums School, Mansoorabad,
Vanasthalipuram, Hyderabad-500070
Tel: +91-40-20064356, +91-9985522558,
+91-9985577886, Fax: +91-40-24024260
E-Mail: hyderabad@kei-ind.com

Guwahati
KEI Industries Limited
H. No-40, Ambika Giri Path, Hatigarh Chariali,
Zoo Narangi Road, Guwahati - 781021, Assam
Mr. Rubul Gogoi: 81348 46024 / 97060 81442
E-mail: northeast@kei-ind.com

Bhubaneswar
KEI Industries Limited
Plot No- 139, 3rd Floor, Rose Dale District Centre,
Chandrashekharpur, Bhubaneswar-751016, Odisha
Tel: +91-9903027514 / 9637138876
E-Mail: odisha@kei-ind.com

Singapore
KEI Industries Limited
No.52, UBI Avenue 3, # 04-37 Frontier,
Singapore-408867 Tel: +65 83240193
Contact: Mr. Xavier Toh Hong Ghee
E-mail: xavier@kei-sin.com



KEI

Wires and Cables

NO OVERLOAD. NO SHORT CIRCUIT. NO TENSION.



FLAME RETARDANT PVC INSULATED SINGLE CORE UNSHEATHED COPPER CABLES (UP TO 1100 VOLTS AC)



CONDUCTOR: The conductors, drawn from bright electrolytic grade copper and annealed and bunched together.

INSULATION: The bunched conductors are insulated with specially formulated FR PVC compound with a high insulation resistance value. The insulation process is carried out on modern high speed extrusion lines, which ensures high accuracy and consistency in performance. Flame retardant properties enable the cable to withstand overloads. The insulation is resistant to boiling water, steam and vapors. This prevents ageing and cracking in kitchens, bathrooms, damp walls and chemical industries.

MARKING: The cables are printed with generic marking 'HOMECAB'.

COLORS: Red, Yellow, Blue, Black, Green and Grey.

PACKING: 90 Meters (apprx.100 yards) pack in protective cartons.

HomeCab is a multi-stranded flexible wire with flame retardant properties. It has specially formulated insulation with a high oxygen and temperature index, enabling the wire to withstand overloads preventing electric mishaps. So, give yourself the promise of security and supreme quality. Get KEI house wires and safeguard your home for life.

homecab™ - FR Flame Retardant

Test	Specification	Specified Values
Critical Oxygen Index	ASTM-D 2863	Minimum 29%
Temperature Index	ASTM-D 2863	Minimum 250 °C

SIZE DIMENSIONS AND RATINGS

Nominal Cross Sectional Area of Conductor	Number/Nominal Dia of wires* [Nom.]	Thickness of insulation [Nom.]	Overall Diameter Max.	Current Rating		D.C Resistance [Max.] at 20 °C
				Casing	Concealed	
Sq.mm	Number/mm	Mm	Mm	amps	amps	Ohm/km
0.75	24/0.2	0.6	2.8	7.50	7.00	26.0
1.00	32/0.2	0.6	3.0	12.00	11.00	19.5
1.50	30/0.25	0.6	3.4	16.00	14.00	13.3
2.50	50/0.25	0.7	4.1	22.00	19.00	7.98
4.00	56/0.3	0.8	4.8	29.00	26.00	4.95
6.00	84/0.3	0.8	5.3	37.00	31.00	3.30

*The number & diameter of conductor strands are for reference only and governed by conductor resistance.
The above data is indicative only and may be revised without prior information. KEI will not be responsible for any damages arising out of incorrect application of its product.

FLAME RETARDANT LOW SMOKE PVC INSULATED SINGLE CORE UNSHEATHED COPPER CABLES (UP TO 1100 VOLTS AC)



CONDUCTOR: The conductors, drawn from bright electrolytic grade copper and annealed and bunched together.

INSULATION: The bunched conductors are insulated with specially formulated Flame Retardant Low Smoke Compound. During a fire situation, the FR-LSH compound restricts the spread of flame. The smoke emission is also minimal.

MARKING: The cables are printed with generic marking 'CONFLAME'.

COLORS: Red, Yellow, Blue, Black, Green and Grey.

PACKING: 90 Meters (apprx.100 yards) pack in protective cartons.

KEI's innovative offering Conflame is ideal for wiring solutions in multi-storied buildings, hotels, hospitals, commercial establishments and residential complexes. It is shielded by a specially formulated flame retardant PVC compound. During fire, ordinary PVC emits black smoke and toxic fumes which are acidic in nature. This impairs visibility and hampers rescue operations. Conflame insulation retards spread of fire and emits minimum smoke and toxic gases. Thereby reducing the risk of injury. So, give yourself the promise of security and supreme quality. Get KEI house wires and safeguard your home for life.

conFlame™ - FRLS Flame Retardant Low Smoke

Test	Specification	Specified Values
Critical Oxygen Index	ASTM-D 2863	Minimum 29%
Temperature Index	ASTM-D 2863	Minimum 250 °C
Acid Gas Generation	IEC 60754-1	Maximum 20%
Smoke Density Rating	ASTM-D 2843	Maximum 60%

SIZE DIMENSIONS AND RATINGS

Nominal Cross Sectional Area of Conductor	Number/Nominal Dia of wires* [Nom.]	Thickness of insulation [Nom.]	Overall Diameter Max.	Current Rating		D.C Resistance [Max.] at 20 °C
				Casing	Concealed	
Sq.mm	Number/mm	Mm	Mm	amps	amps	Ohm/km
0.75	24/0.2	0.6	2.8	7.50	7.00	26.0
1.00	32/0.2	0.6	3.0	12.00	11.00	19.5
1.50	30/0.25	0.6	3.4	16.00	14.00	13.3
2.50	50/0.25	0.7	4.1	22.00	19.00	7.98
4.00	56/0.3	0.8	4.8	29.00	26.00	4.95
6.00	84/0.3	0.8	5.3	37.00	31.00	3.30

*The number & diameter of conductor strands are for reference only and governed by conductor resistance.
The above data is indicative only and may be revised without prior information. KEI will not be responsible for any damages arising out of incorrect application of its product.

ZERO HALOGEN FLAME RETARDANT INSULATED SINGLE CORE UNSHEATHED COPPER CABLES (UP TO 1100 VOLTS AC)



CONDUCTOR: The conductors, drawn from bright electrolytic grade copper and annealed and bunched together.

INSULATION: The bunched conductors are insulated with specially formulated grade of Halogen Free Flame Retardant (HFFR) compound is used. The insulation does not melt or drop in case of fire. The smoke emitted is transparent, non-toxic and minimal. The victims, trapped in the fire do not suffocate and evacuation is convenient.

MARKING: The cables are printed with generic marking 'BANFIRE'.

COLORS: Red, Yellow, Blue, Black, Green and Grey.

PACKING: 90 Meters (apprx.100 yards) pack in protective cartons.

KEI Banfire is processed using a zero Halogen Flame Retardant compound (ZHFR). The insulation is of superior quality, 100% PVC free and eco-friendly. In case of a fire situation, Banfire does not emit toxic or poisonous fumes, which enables safe evacuation. These wires are best suited for wiring in hospitals, hotels, business establishments and high rise buildings where fire can be determined. So, give yourself the promise of security and supreme quality. Get KEI house wires and safeguard your home for life.

banFire™ - ZHFR Zero Halogen Flame Retardant

Test	Specification	Specified Values
Critical Oxygen Index	ASTM-D 2863	Minimum 29%
Temperature Index	ASTM-D 2863	Minimum 250 °C
Acid Gas Generation	IEC 60754-1	Maximum 0.5%
Smoke Density Rating	ASTM-D 2843	Maximum 20%

SIZE DIMENSIONS AND RATINGS

Nominal Cross Sectional Area of Conductor	Number/Nominal Dia of wires* [Nom.]	Thickness of insulation [Nom.]	Overall Diameter Max.	Current Rating		D.C Resistance [Max.] at 20 °C
				Casing	Concealed	
Sq.mm	Number/mm	Mm	Mm	amps	amps	Ohm/km
0.75	24/0.2	0.6	2.8	7.50	7.00	26.0
1.00	32/0.2	0.6	3.0	12.00	11.00	19.5
1.50	30/0.25	0.6	3.4	16.00	14.00	13.3
2.50	50/0.25	0.7	4.1	22.00	19.00	7.98
4.00	56/0.3	0.8	4.8	29.00	26.00	4.95
6.00	84/0.3	0.8	5.3	37.00	31.00	3.30

*The number & diameter of conductor strands are for reference only and governed by conductor resistance.
The above data is indicative only and may be revised without prior information. KEI will not be responsible for any damages arising out of incorrect application of its product.